



BAMBI BUCKET VALVES



POWERFILL ACCESSORIES



Bambi Power Pack™

A portable, rechargeable power supply used with Bambi Bucket and Bambi MAX allowing them to be operated independently of the helicopter power supply.



Cover: Bambi Torrentula Bucket with

PowerFill flown by Coulson Aircrane

to battle Black Saturday bushfires -


Right: Valhalla Helicopters using

PowerFill Snorkel to access shallow

SAU, State of Victoria.

PowerFill™

Designed specifically for Bambi Buckets; available in externally mounted snorkel or integrated into Bambi Max, Torrentula Valves. Allows bottom-filling capability from as little as 18 inches (45 cm) of water. Provides for quicker turn times by accessing shallow water sources and facilitating quicker dips. Also allows for load control at dip sites.



The Modular Case is a selfcontained hard case rackmount system, designed for plug n' play and easy storage of Torrentula Controller, PowerFill Controller and Remote Power Supply.



Sacksafoam[™] Systems


The Sacksafoam is a foam injection system designed for simple transfer and dispensing of aerial firefighting foam in a bucket. Allows for precise, reliable foam injection to enhance your drop effectiveness on the fireline.



operation with a rugged, lightweight design. Easy to steer and brake, the threewheeled aluminum mobility cart comes equipped with 16" foam-filled, all-terrain tires, a tow bar and can be quickly dismantled for shipping. Roll













SPECIFICATIONS & COMPATIBILITY

																		& S				
			/ ,	PROTECT /	/ ka	T CHILLIAN /	/ g .	S ELL		7 2 5	: /		6 , 4	-/*	le constant de la con		e suc				QUE .	Sing September 1
		\ \\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\						2	, te		7000	Solito de la constitución de la	S S S S S S S S S S S S S S S S S S S	Por Workill II	Per III S.	0000	60,60,60	Saloan In those	Sec los	16 18 18 18 18 18 18 18 18 18 18 18 18 18	30 1 5 8 0 1 1 0 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	Solve
	BB 6072	72	270	68	31	670	300	12'11"	394		•	•								•	•	
	BB 8096	96	360	71	32	870	390	14'6"	442		•	•				•	•		•	•	•	
	BB 9011	108	410	72	32	970	440	14'6"	442	•	•	•				•	•		•	•	•	
	BB 1012	120	450	71	32	1070	490	14'6"	442	•	•	•				•	•		•	•	•	
	BB 1214	144	550	73	33	1270	580	14'10"	452	•	•	•				•	•		•	•	•	
X BAMBI BUCKET	BB 1518	180	680	76	34	1580	710	15'2"	462	•	•	•				•	•		•	•	•	
	BB 1821	216	820	86	39	1890	860	15'11"	470	•	•	•		•		•	•		•	•	•	
	BB 2024	240	910	127	58	2130	960	20'1"	592	•	•	•		•		٠	•		•	•	•	
	BB 2226	260	1000	125	57	2330	1050	15'10"	470	•	•	•		•		•	•		•	•	•	
	BB 2732	320	1230	134	61	2830	1290	23'0"	701	•	•	•		•		•	•		•	•	•	oxdot
	BB 3542	420	1590	142	64	3640	1650	23'8"	714	•	•	•		•		•	•		•	•	•	
	BB 4453	530	2000	180	80	4580	2080	23'8"	721	•	•	•		•		•	•	•	•	•	•	
	BB 5566	660	2500	260	120	5760	2610	24'7"	749	•	•	•				•	•	•	•	•	•	
	BB 6578	780	2950	300	140	6800	3090	25'1"	763	•	•	•				•	•	•	•	•	•	
	BB 7590	900	3410	320	150	7820	3550	30'6"	930	•	•	•				•	•	•	•	•	•	
	BBHL 4000	1060	4000	360	160	9160	4150	31'8"	965	•	•	•				•	•	•	•	•	•	
	BBHL 5000	1320	5000	380	170	11370	5160	32'0"	975	•	•	•				•	•	•	•	•	•	
	BBHL 7600	2010	7600	450	210	17170	7790	33'1"	1008	•	•	•				•	•	•	•	•	•	
	BBHL 9800	2590	9800	510	230	22070	10010	34'3"	1044	•		•				•	•	•	•	•	•	
	BBX 1518	180	680	93	42	1590	720	13'5"	408			•								•		
	BBX 1821	216	820	102	46	1900	860	13'7"	414													
	BBX 2024	240	910	137	62	2140	970	16'7"	505			•		•		•	•					
	BBX 2226	260	1000	135	61	2330	1060	13'0"	396			•										
	BBX 2732	320	1230	145	66	2840	1290	19'11"	607		•	•		•		•	•		•	•	•	
ĕ '	BBX 3542	420	1590	152	69	3650	1660	20'9"	632								•		•			
_	BBX 4453	530	2000	220	100	4620	2100	23'8"	721	•	•	•	•	-		•	•		•	•	•	
Θ.	BBX 5566	660	2500	290	130	5790	2630	24'7"	749													
BAMBI MAX	BBX 6578	780	2950	330	150	6830	3100	25'1"	763	•	•	•	•			•	•	•	•	•	•	
	BBX 7590	900	3410	350	160	7850	3560	30'6"	930				•			•	•		•	•		
	BBXHL 4000	1060	4000	370	170	9170	4160	31'8"	965	•	•	•	•			•	•	•	•	•	•	
	BBXHL 5000	1320	5000	380	170	11380	5160	32'0"	975													
	BBXHL 7600	2010	7600	470	210	17190	7800	33'1"	1008	•	•	•	•			•		•	•	•	•	
	BBXHL 9800	2590	9800	530	240	22080	10020	34'3"	1044													
								""														
	DDT	F-0-0	0000	655	400	4000	0.115	00101														
4	BBT 4453	530	2000	250	120	4650	2110	23'8"	721	•	•		•		•	•	•		•	•	•	
<u> </u>	BBT 5566	660	2500	400	180	5900	2670	24'7"	749	•	•		•		٠	٠		•	•	٠	•	
5	BBT 6578	780	2950	430	200	6930	3140	25'1"	763	•	•		•		•	•		•	•	•	•	
TORRENTULA	BBT 7590	900	3410	460	210	7960	3610	30'6"	930	٠	•		•		٠	٠		•	٠	•	•	
	BBTHL 4000	1060	4000	490	220	9290	4210	31'8"	965	•	•		•		•	•		•	•	•	•	
	BBTHL 5000	1320	5000	500	230	11500	5220	32'0"	975	٠	•		•		٠	٠		•	٠	•	•	
	BBTHL 7600	2010	7600	580	260	17300	7840	33'1"	1008	•	•		•		•	•		•	•	•	•	
	BBTHL 9800	2590	9800	640	290	22190	10070	34'3"	1044	•			•		•	•		•	•	•	•	

Specifications are subject to change without notice

* Overall lengths are accurate to within 1% overall lengths with standard rigging

* Overall lengths listed are of basic bucket models without PowerFill installed



